



MODEL		TOP KFW - 68.2 GH				TOP KFW - 68.3 GH				TOP KFW - 68.4 GH				
Protok vazduha		6100 m ³ /h				5400m ³ /h				5300m ³ /h				
G/H	Režim vode	Tul. [°C]	Q [kW]	Tiz [°C]	Δp [kPa]	q _w [m ³ /h]	Q [kW]	Tiz [°C]	Δp [kPa]	q _w [m ³ /h]	Q [kW]	Tiz [°C]	Δp [kPa]	q _w [m ³ /h]
HLAĐENJE	7/12°C	25(50%)	11.03	19.6	6.28	1.86	13.47	17.6	4.89	2.27	15.51	16.3	4.16	2.61
		27(47%)	12.85	20.7	8.06	2.16	15.77	18.3	6.24	2.65	18.22	16.7	5.26	3.07
		32(39%)	17.43	23.3	13.37	2.93	21.29	20.1	10	3.57	24.66	17.9	8.24	4.14
		35(33%)	20.05	24.9	16.95	3.37	24.47	21.1	12.52	4.11	28.44	18.6	10.26	4.77
	12/17°C	25(50%)	6.57	21.8	2.68	1.11	7.91	20.6	2.17	1.34	8.73	20.1	1.85	1.47
		27(47%)	8.51	22.8	4.05	1.44	10.38	21.3	3.24	1.75	11.88	20.3	2.82	2
		32(39%)	13.13	25.5	8.17	2.21	16.07	23	6.3	2.7	18.68	21.3	5.37	3.14
		35(33%)	15.83	27.1	11.15	2.66	19.35	24	8.44	3.26	22.51	22	7.09	3.79
GREJANJE	45/40°C	-15	48.86	8.9	73.36	8.5	59.8	18.1	52.37	10.4	69.89	24.4	41.56	12.15
		-10	44.46	11.8	62.15	7.73	54.44	20.1	44.6	9.47	63.65	25.9	35.59	11.07
		-5	40.06	14.6	51.78	6.97	49.07	22.1	37.39	8.53	57.41	27.3	30.04	9.98
		0	35.66	17.5	42.28	6.2	43.71	24.2	30.75	7.6	51.17	28.8	24.9	8.9
		5	31.26	20.3	33.65	5.44	38.33	26.2	24.68	6.67	44.95	30.3	20.2	7.82
		10	26.86	23.1	25.91	4.67	32.97	28.2	19.22	5.73	38.71	31.8	15.92	6.73
		15	22.45	26	19.06	3.9	27.59	30.3	14.35	4.8	32.45	33.3	12.08	5.64
		20	18.04	28.8	13.18	3.14	22.23	32.3	10.13	3.87	26.17	34.7	8.69	4.55
	55/45°C	-15	53.98	11.4	25.68	4.71	66.26	21.6	19.09	5.78	77.81	28.8	15.87	6.78
		-10	49.58	14.3	22.2	4.32	60.9	23.7	16.62	5.31	71.56	30.3	13.91	6.24
		-5	45.16	17.1	18.93	3.94	55.53	25.7	14.3	4.84	65.3	31.8	12.06	5.69
		0	40.75	19.9	15.91	3.55	50.15	27.7	12.12	4.37	59.03	33.3	10.32	5.15
		5	36.35	22.8	13.12	3.17	44.8	29.8	10.11	3.91	52.76	34.7	8.7	4.6
		10	31.93	25.6	10.56	2.78	39.42	31.8	8.25	3.44	46.46	36.2	7.19	4.05
	70/50°C	-15	60.03	14.4	9.35	2.63	74.16	26.0	7.38	3.25	87.52	34.3	6.5	3.83
		-10	55.59	17.2	8.23	2.43	68.73	28.0	6.56	3.01	81.2	35.7	5.82	3.55
-5		51.17	20	7.18	2.24	63.32	30	5.78	2.77	74.87	37.2	5.17	3.28	
0		46.74	22.1	6.20	2.05	57.88	32.0	5.03	2.53	68.53	38.6	4.55	3	
5		42.29	25.7	5.27	1.85	52.42	34	4.33	2.29	62.15	40	3.96	2.72	
10		37.84	28.5	4.40	1.66	46.96	36.0	3.67	2.06	55.75	41.4	3.4	2.44	
15		33.36	31.3	3.60	1.46	41.46	37.9	3.05	1.81	49.28	42.8	2.86	2.16	
20		28.86	34.1	2.82	1.26	35.91	39.9	2.47	1.57	42.8	44.1	2.36	1.87	
80/60°C	-15	69.33	18.9	11.67	3.05	85.54	32.3	9.11	3.76	100.84	41.8	7.94	4.43	
	-10	64.92	21.8	10.46	2.85	80.15	34.3	8.22	3.52	94.55	43.3	7.22	4.15	
	-5	60.51	24.6	9.31	2.66	74.74	36.3	7.37	3.28	88.25	44.7	6.52	3.88	
	0	56.09	27.5	8.21	2.46	69.32	38.3	6.55	3.05	81.95	46.2	5.84	3.6	
	5	51.64	30.3	7.17	2.27	63.92	40.3	5.78	2.81	75.63	47.6	5.2	3.32	
	10	47.22	33.1	6.19	2.07	58.48	42.3	5.05	2.57	69.29	49	4.58	3.04	
	15	42.78	35.9	5.28	1.88	53.05	44.3	4.35	2.33	62.93	50.4	4	2.77	
	20	38.32	38.8	4.42	1.68	47.57	46.3	3.7	2.09	56.53	51.8	3.44	2.48	
90/70°C	-15	78.57	23.5	14.16	3.47	96.72	38.5	10.93	4.27	114.02	49.2	9.47	5.03	
	-10	74.16	26.3	12.85	3.27	91.37	40.5	9.98	4.03	107.75	50.7	8.69	4.75	
	-5	69.75	29.1	11.59	3.08	85.98	42.5	9.07	3.79	101.47	52.2	7.94	4.48	
	0	65.34	32.0	10.4	2.88	80.65	44.6	8.2	3.56	95.19	53.6	7.22	4.2	
	5	60.92	34.8	9.26	2.69	75.25	46.6	7.35	3.32	88.9	55.1	6.52	3.92	
	10	56.50	37.7	8.17	2.49	69.86	48.6	6.55	3.08	82.59	56.5	5.86	3.64	
	15	52.06	40.5	7.15	2.3	64.43	50.6	5.78	2.84	76.28	58	5.22	3.37	
	20	47.63	43.3	6.18	2.1	59.02	52.6	5.06	2.6	69.94	59.4	4.61	3.09	